

Mission Technology Forum

Section 5

Advanced Land Imager (ALI) Design Overview


This work was sponsored by NASA Goddard Space flight Center under U.S. Air Force Contract number F19628-00-C-0002. Opinions, interpretations, conclusions and recommendations are those of the author and are not necessarily endorsed by the United States Government.



08/15-16/01

. . . Don E. Lencioni

Massachusetts Institute of Technology Lincoln Laboratory



Topics of Discussion




Mission Technology Forum

- ◆ *Introduction*
- ◆ *Key specifications*
- ◆ *Technology description*
- ◆ *Design overview*
- ◆ *Summary*



08/15-16/01



Introduction




Mission Technology Forum

- ◆ ***Primary instrument on the first Earth Observing Mission (EO-1) of NASA's New Millennium Program (NMP)***
- ◆ ***Objectives are to flight validate key technologies***
 - *Data continuity, advanced capability and cost reduction for future Landsat instruments*
 - *Innovative approaches to future land imaging*
- ◆ ***The ALI instrument was designed and developed by MIT Lincoln Laboratory with NMP instrument team members***
 - *Raytheon SBRS for the focal plane system*
 - *SSG Inc. for the optical system*



08/15-16/01




Instrument Design Process



Mission Technology Forum

- ◆ *Instrument architecture emerged from technologies represented on the NMP IPDT*
- ◆ *Flight validation was required to significantly reduce the risk for future missions*
- ◆ *Design must be scaleable to a full-up instrument*
- ◆ *Flight data must be amenable to science validation*
- ◆ *Measurement requirements were developed*
 - *From the bottom up by the IPDT*
 - *In collaboration with the earth science community*






Key ALI Specifications



Mission Technology Forum

- ◆ ***Meet or exceed ETM+ performance (w/o thermal band) at minimum size, weight, schedule, and cost***
- ◆ ***Spectral band suite was augmented for science reasons***
 - ***Split band # 4 into two sub-bands***
 - ***Add bands at 442 nm and 1244 nm***
 - ***Reduce spectral width on the Pan band***
- ◆ ***Pan band GSD reduced to 10m***
- ◆ ***Dynamic range to cover >100% albedo with one gain state***
- ◆ ***Minimum sensor size driven by image sharpness (MTF)***
- ◆ ***SNR four to ten times ETM+ values, depending on band***
- ◆ ***Demonstrate spatial, spectral, and radiometric calibration for large detector arrays***
- ◆ ***Other performance goals guided by Landsat-7***







Advanced Land Imager (ALI)



Mission Technology Forum



08/15-16/01





ALI Optical Design Form




Mission Technology Forum

- ◆ **All reflective Cooke Triplet**
 - *Aspheric primary*
 - *Ellipsoidal secondary*
 - *Spherical tertiary*
- ◆ **Aperture stop on secondary mirror**
- ◆ **Non-relayed design**
- ◆ **Near telecentric**
- ◆ **FOV = 1.256 x 15 degrees**




08/15-16/01




Main Focal Plane Assembly



Mission Technology Forum






ALI Spectral Response Functions




Mission Technology Forum



ALI Bands	1p	1	2	PAN	3	4	4p	5p	5	7
Wavelength (nm)	442	485	567	592	660	790	866	1244	1640	2226
Bandwidth (nm)	19	53	70	144	56	31	44	88	171	272




08/15-16/01




MS/PAN Flight Module



Mission Technology Forum



08/15-16/01




Main Focal Plane Assembly



Mission Technology Forum


MAIN FOCAL PLANE ASSEMBLY, EO-1



98-06-053




08/15-16/01



Partially Assembled Flight ALI



Mission Technology Forum




◆ *Telescope features*

- *12.5 cm entrance pupil*
- *15° x 1.26° field-of-view*
- *Telecentric, f/7.5 design*
- *Unobscured, reflective optics*
- *Silicon carbide mirrors*
- *Wavefront error: = 0.11 λ RMS @ 633 nm*




08/15-16/01




Internal Reference Source



Mission Technology Forum



08/15-16/01




Internal Reference Source



Mission Technology Forum




Lamp Assembly



Lamp Installation




08/15-16/01




Optical Arrangement, Main FPA



Mission Technology Forum




08/15-16/01




Detector Response to Reference Source



Mission Technology Forum






08/15-16/01




Solar Calibration



Mission Technology Forum




08/15-16/01




Calibration Diffuser Mechanism



Mission Technology Forum




08/15-16/01




Aperture Selector Mechanism



Mission Technology Forum



08/15-16/01




ALI Flight Instrument



Mission Technology Forum




08/15-16/01




ALI as Delivered on March 16, 1999



Mission Technology Forum



08/15-16/01



Summary



Mission Technology Forum

- ◆ ***ALI is the primary instrument on the EO-1 mission of NASA's New Millennium Program***
- ◆ ***Comprehensive pre-launch characterization and calibration were conducted***
- ◆ ***The mission is now in progress and is successfully validating ALI technologies***
- ◆ ***Key performance specifications have been met***
- ◆ ***ALI provides path for low cost, high performance, remote sensing instruments***

